

22.5 mm Push Button Enclosures Specifications

1



Bulletin 598 — 22.5 mm Push Button Enclosure

- Pre-molded 22.5 mm mounting hole
- Available in two colors:
 - Grey enclosures: Type 4, 4X, 12, and 13 watertight, corrosion resistant, and dusttight, IP66 protection
 - Yellow enclosures: Type 4, 4X, 12, and 13 watertight, corrosion resistant, and dusttight, IP66 protection
- Available in these configurations:
 - 1-hole
 - 2-hole
 - 3-hole
 - 4-hole
- Designed for both indoor and outdoor applications

Table of Contents

Specifications..... this page
 Product Selection..... 1-255
 Approximate Dimensions..... 1-258

Standards Compliance

UL 508A
 CSA C22.2, No. 14


Certifications

cULus Listed (File No. E54866;
 Guide No. NITW, NITW7)
 CE Marked

Technical Specifications


Product Certification	
Approvals/Certifications	cULus, CE
Degree of Protection	Type 4, 4X, 12, and 13, IP66
Environmental	
Storage Temperature Range	-40...+75 °C (-40...+158 °F)
Operating Temperature Range	-40...+55 °C (-40...+131 °F)
Material	
Enclosure	Thermoplastic polyester blend, UL94 5VA
Gasket	Foam-in-place polyurethane

Legend Plate Compatibility/Options



22.5 mm Push Button Enclosure

Contact Block Compatibility/Options



22.5 mm Push Button Enclosure

Note: Pictures are for illustrative purposes only, depicting suitable legend plates and contact blocks that would fit in and on the Bul. 598/800H push button plastic enclosure. Please reference the appropriate selection guides for more dimensional information.

22.5 mm Push Button Enclosures

Product Selection



Cat. No. 598-1PB22



Cat. No. 598-2PB22

Enclosure	Cat. No.	Pkg. Quantity	Cat. No.	Pkg. Quantity
Grey Enclosure	598-1PB22G	1	598-2PB22G	1
Yellow Enclosure	598-1PB22Y		598-2PB22Y	
Outside Dimensions* (H x W x D)	110 mm x 80 mm x 85 mm (4.33 in. x 3.15 in. x 3.35 in.)		130 mm x 80 mm x 85 mm (5.12 in. x 3.15 in. x 3.35 in.)	
Base Depth	50 mm (1.97 in.)		50 mm (1.97 in.)	
Cover Depth	35 mm (1.38 in.)		35 mm (1.38 in.)	
Cover Screw Material	Glass-reinforced nylon		Glass-reinforced nylon	
Recommended Tightening Torque	1.0...1.2 N•m (9...11 lb•in)		1.0...1.2 N•m (9...11 lb•in)	
Approx. Ship Weight	232 g (0.51 lb)		271 g (0.60 lb)	



Cat. No. 598-3PB22



Cat. No. 598-4PB22

Enclosure	Cat. No.	Pkg. Quantity	Cat. No.	Pkg. Quantity
Grey Enclosure	598-3PB22G	1	598-4PB22G	1
Yellow Enclosure	598-3PB22Y		598-4PB22Y	
Outside Dimensions* (H x W x D)	180 mm x 80 mm x 85 mm (7.09 in. x 3.15 in. x 3.35 in.)		250 mm x 80 mm x 85 mm (9.84 in. x 3.15 in. x 3.35 in.)	
Base Depth	50 mm (1.97 in.)		50 mm (1.97 in.)	
Cover Depth	35 mm (1.38 in.)		35 mm (1.38 in.)	
Cover Screw Material	Glass-reinforced nylon		Glass-reinforced nylon	
Recommended Tightening Torque	1.0...1.2 N•m (9...11 lb•in)		1.0...1.2 N•m (9...11 lb•in)	
Approx. Ship Weight	357 g (0.79 lb)		435 g (0.96 lb)	

Note: Holes are pre-molded to fit 22.5 mm push buttons, such as the Allen-Bradley Bulletin 800F.

* Dimensions are not intended to be used for manufacturing purposes.

For information on legend plates and contact blocks, see Legend Plate Compatibility/Options and Contact Block Compatibility/Options on page 1-256.