



Project: Ecommerce

Routeco Ltd
 Davy Avenue
 Knowhill
 Milton Keynes
 MK5 8HJ

TY232M

Premium cable tie with stainless steel locking barb to cover the most demanding applications.

T&B Catalog Number: TY232M
EAN Number: 05414363061410
UPC Number: 78621083069
Description: Premium, standard cable tie, 203 x 2.4 mm, natural Polyamide 6.6



Technical Information

Type	standard
Material	Polyamide 6.6
Material Locking Barb	316 grade stainless steel
Temperature Range	-40°C to +85°C
Flammability Rating	UL 94 V-2
Colour	natural
Halogen free	yes
Silicone free	yes

Approvals

UL listed	E49405
Germanischer Lloyd approval	yes
Lloyds Register approval	yes
Other approval	BVQ

Ordering Information

Length (mm)	203
Width (mm)	2.4
Thickness (mm)	1
Max. Bundle Diameter (mm)	50
Min. Bundle Diameter (mm)	2
Min. Tensile Strength (N)	80

Quantity (pieces)	1000
Packaging Type	bag
Storage Conditions	Nylon (Polyamide) is inherently susceptible to environmental conditions. Polyamide 6.6 cable ties are moisturised to optimum performance levels at machine-side and should be stored in cool dry areas out of direct sunlight. Cable ties are packaged in plastic bags to contain moisture and should remain sealed until ready for use.
Tooling	ERG50, WT193A
