

Standard T&B Catalog Number:

TY27MX

UPC Number: 78621082478 Status: Active

Description:

Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 340.4mm (13.4 Inches), Width of 7.0mm (0.27 Inches), Thickness of 1.65mm (0.06 Inches), Tensile Strength Rating of 530 Newtons (120 Pounds), Military Specified (MIL-SPEC MS3367-3-0), Bulk Pack

| tons (120 Pounds), Military Spe | cified (MIL-SPEC MS3367-3-0), Bulk Pack |
|------------------------------------|--|
| Features | |
| | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. Because there are no notches, Ty-Rap ties provide an infinite number of locking positions while fastening the tie at the precise bundle diameter needed. The No-Slip Tail provides easy grip during tensioning. Ty-Rap ties feature a unique friction surface de- |
| | signed to reduce slippage during installation. |
| General | Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables. |
| | N.L. COW d. D. i.e. |
| Material | Nylon 6.6 Weather Resistant |
| Color | Black |
| Dimension Information | |
| Nominal Length (inches) | 13 |
| Length (inches) | 13.4 |
| Width (inches) | .270 |
| Max. Wire Bundle Diameter (inches) | 3.5 |
| Specifications | |
| Military Standard Part No. | MS3367-3 |
| Temperature Rating | -40°F to 185°F |
| Flammability Rating | UL 94 V-2 |
| Tooling | OL 94 V-2 |
| Tooming | |
| Application Tools | ERG120, WT197 |
| Packaging | |
| T&B Order Multiple | 500 |
| T&B Inner Pack | 500 |
| Package in Units | 1000 |
| Package Type | Bulk |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 0.94 lbs. per 100 |
| | |



Application Support Material Selection Guide Available on Website Available Colors Available on Website Certifications RoHS Compliance Yes Certifications



File Nbr: E49405

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

 ${\bf Email: tech support@tnb.com}$

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com