

Flame Retardant T&B Catalog Number:

TY23MFR

UPC Number: 78621080105

Status: Active

Description:

Cable Tie, Flame Retardant White Nylon 6.6 for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 91.95mm (91.95 Inches), Width of 2.36mm (0.093 Inches), Thickness of 0.77mm (0.03 Inches), Tensile Strength Rating of 80 Newtons (18 Pounds)

o . ou
Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulk- heads. Non-magnetic stainless steel locking device insures both maximum strength and the right tight- ness every time.
Because there are no notches, Ty-Rap ties provide
an infinite number of locking positions while fastening the tie at the precise bundle diameter needed.
The No-Slip Tail provides easy grip during tension-
ing. Ty-Rap ties feature a unique friction surface designed to reduce slippage during installation.
Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.
Nylon 6.6 Flamo Potardant
Nylon 6.6 Flame Retardant White
vviille
4
3.62
.091
.625
-40°F to 185°F
UL 94 V-0
ERG50, WT1-TB
1000
1000
10000
Bulk
Each
0.63 lbs. per 1000
Available on Website



Certifications

RoHS Compliance

Yes

Certifications



File Nbr: E49405

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

8155 T&B Blvd. Memphis, TN 38125 www.tnb.com

Thomas & Betts - USA