

Atlantic metal cabinets

IP 55/IP 66 - IK 10 - Type 4x - Type 12



0 369 19



0 369 79



0 369 28



0 355 53

Cabinet and equipment selection chart **p. 288**
 Technical characteristics **p. 295**

IP 66 according to standards IEC EN 60529 for 1-door cabinets - IP 55 according to standards IEC EN 60529 for 2-door cabinets
 IK 10 according to standards IEC EN 62262
 LCIE 17 07 90 10A

Type 4x, 1 door, Type 12, 2 doors - cULus, Bureau Veritas
 EMC attenuation 20 dB (for an EMC attenuation from 40 to 50 dB at 1 GHz, please consult us)

Excellent resistance to corrosion and chemical agents

80 µm thick textured polyester coating. Anti-corrosion treatment for hinges and pins

Reversible door - Fitted with lever

Supplied with : Double bar lock - Self-centering positioning system for the equipment

Compatible with all Atlantic accessories

Low cable entries RAL 7035 - Optional depth adjustment for cabinets 400 mm depth, with slide rails Cat.No 0 367 45 (p. 292)

Pack	Cat.Nos	Metal door cabinets			Pack	Cat.Nos	Glass door cabinets		
		Supplied with plain plate					Vertical version		
		Vertical version					Vertical version		
		External dimensions (mm) Height x Width x Depth	Number of doors	Weight (kg)		N	External dimensions (mm) Height x Width x Depth	Number of doors	Weight (kg)
1	0 369 10 ¹	300 x 200 x 160	1	3.9	1	0 369 27	400 x 300 x 200	1	6.9
1	0 369 12 ¹	400 x 300 x 160	1	6.3	1	0 369 28	500 x 400 x 200	1	11.2
1	0 369 13	500 x 400 x 160	1	10.3	1	0 369 29	600 x 400 x 200	1	13
1	0 369 17	400 x 300 x 200	1	6.9	1	0 369 36	600 x 400 x 250	1	14
1	0 369 18	500 x 400 x 200	1	11.2	1	0 369 40	700 x 500 x 250	1	23.8
1	0 369 19	600 x 400 x 200	1	13	1	0 369 41	800 x 600 x 250	1	30.9
1	0 369 20	600 x 500 x 200	1	16.8	1	0 369 47	800 x 600 x 300	1	32
1	0 369 21	700 x 500 x 200	1	20.3	1	0 369 48	1000 x 600 x 300	1	45
1	0 369 25	500 x 400 x 250	1	13.2	1	0 369 49	1000 x 800 x 300	1	56.9
1	0 369 26	600 x 400 x 250	1	14	1	0 369 56	1200 x 800 x 400	1	73.6
1	0 369 30	700 x 500 x 250	1	23.8	1	0 369 60	1400 x 800 x 400	1	81.6
1	0 369 31	800 x 600 x 250	1	30.9	1		Square version		
1	0 369 32	1000 x 600 x 250	1	44.5	1	0 369 74	600 x 600 x 250	1	22.8
1	0 369 33	1000 x 800 x 250	1	49.5			Roofs RAL 7035		
1	0 369 37	800 x 600 x 300	1	32			Steel		
1	0 369 38	1000 x 600 x 300	1	45			Possible adjustment ± 20 mm (front or back)		
1	0 369 39	1000 x 800 x 300	1	56.9			For cabinets		
1	0 369 42	1200 x 600 x 300	1	50.4			Width (mm)	Depth (mm)	Weight (kg)
1	0 369 43	1200 x 800 x 300	1	67	1	0 365 52	400	200	1.4
1	0 369 44	800 x 600 x 400	1	41.6	1	0 365 67	500	200	1.8
1	0 369 45	1000 x 800 x 400	1	63.5	1	0 365 68	600	200	2.1
1	0 369 46	1200 x 800 x 400	1	73.6	1	0 365 53	400	250	1.8
1	0 369 50	1400 x 800 x 400	1	81.6	1	0 365 64	500	250	2
		Square version			1	0 365 54	600	250	2.5
1	0 369 51 ¹	300 x 300 x 160	1	4.8	1	0 365 56	600	300	3
1	0 369 55	300 x 300 x 200	1	5.6	1	0 365 57	800	300	3.6
1	0 369 57	400 x 400 x 200	1	8.7			Plinths RAL 7021		
1	0 369 59	500 x 500 x 200	1	13.6			Height 200 mm		
1	0 369 62	500 x 500 x 250	1	15.2			Front and rear trap door		
1	0 369 64	600 x 600 x 250	1	22.8			For cabinets		
1	0 369 68	800 x 800 x 300	1	48	1	0 363 00	Width (mm)	Depth (mm)	Weight (kg)
1	0 369 72	600 x 600 x 400	1	33.5	1	0 363 01	600	300	6
		Horizontal version					800	300	6.7
1	0 369 11 ¹	300 x 400 x 160	1	6.2			1: With no opening		
1	0 369 75	300 x 400 x 200	1	6.9					
1	0 369 76	400 x 600 x 200	1	13					
1	0 369 77	400 x 600 x 250	1	14					
1	0 369 78	600 x 800 x 300	2	38.4					
1	0 369 79	600 x 1000 x 300	2	47.4					
1	0 369 80	800 x 1000 x 300	2	59.7					
1	0 369 81	1000 x 1200 x 300	2	85.7					