

Rittal – The System.

Faster – better – everywhere.

Door-operated switch – SZ 4127.210

Date : Jan 25, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Door-operated switch – SZ 4127.210

created: 25.01.2019 build on www.rittal.com/uk-en



Product description

Function principle: The toggle is actuated via the tubular door frame of the sheet steel door, or in the case of glazed doors, via an adaptor included with the supply.

Product features

Rated operating voltage: 400 V

Installation options: for TS enclosures with installed large swing frame
for standard and courtesy light

For rated current (max.): 240 V AC, 6 A

Rated insulation voltage: 400 V AC

Rated impulse withstand voltage, phase to phase: 6000 V AC

Packs of: 1 pc(s).

Weight/pack: 0.26 kg

EAN: 4028177581326

Customs tariff number: 85369095

ETIM 6.0: EC002626

ETIM 5.0: EC002626

eCl@ss 8.0/8.1:	27189266
eCl@ss 7.0/7.1:	27119116
eCl@ss 6.0/6.1:	27119116
eCl@ss 5.1/5.1.4:	27189241
Product description:	SZ Door-operated switch, with toggle, without connection cable, UL
Approvals	
Approvals:	CCC CSA
Certificates:	EAC
Declarations:	Declaration of conformity