

Rittal – The System.

Faster – better – everywhere.

Courtesy light – SZ 4139.140

Date : Jan 17, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Courtesy light – SZ 4139.140

created: 17.01.2017 build on www.rittal.com/uk-en



Product description

Supply includes: Courtesy light
Light
Light cover
Assembly parts

Product features

Design: without door operated switch

Dimensions: Width: 452 mm
Height: 117 mm
Depth: 50 mm

Rated operating voltage: 100 V - 240 V, 1~, 50 Hz/60 Hz

Installation options: TS horizontal section of the roof frame: direct
TS, SE vertical section: with TS adaptor bracket
SE sections at the front and rear of the roof frame: with TS adaptor bracket
SE extrusions at the side of the roof frame: direct
AE, CM, TP: with universal bracket
AE: with rail for interior installation

Operating temperature: Operation (environment): -15°C...+45°C
Bearing: -20°C...+70°C

Power consumption: 14 W

Equipment (electrical): Ballast: Wide-range electronic ballast
Light: Fluorescent lamp, base G13
Jack/socket (type): D, earthing-pin (type F, CEE 7/4)
Switch (type): Integral, on/off/door-operated switch mode

Rated insulation voltage:	500 V DC/1s
Rated impulse withstand voltage, phase to earth:	1000 V AC
Rated impulse withstand voltage, phase to phase:	500 V AC
Protection category:	I (PE conductor)
Connection options:	Power supply via connectors Door-operated switch Through-wiring (creating rows of lights)
Light – installation type:	Screw-fastening
Light cover:	yes
Packs of:	1 pc(s).
Weight/pack:	1.6 kg
EAN:	4028177092327
Customs tariff number:	94054095
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity