

Rittal – The System.

Faster – better – everywhere.

Courtesy light – SZ 4139.190

Date : Jan 17, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Courtesy light – SZ 4139.190

created: 17.01.2017 build on www.rittal.com/uk-en



Product description

Supply includes:	Courtesy light Light Light cover Assembly parts Integral door-operated switch
-------------------------	---

Product features

Design:	With door-operated switch
Dimensions:	Width: 682 mm Height: 117 mm Depth: 50 mm
Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz
Installation options:	TS horizontal section of the roof frame: direct TS, SE vertical section: with TS adaptor bracket SE sections at the front and rear of the roof frame: with TS adaptor bracket SE extrusions at the side of the roof frame: direct
Operating temperature:	Operation (environment): -15°C...+45°C Bearing: -20°C...+70°C
Power consumption:	18 W
Equipment (electrical):	Ballast: Wide-range electronic ballast Light: Fluorescent lamp, base G13 Jack/socket (type): D, earthing-pin (type F, CEE 7/4) Integral door-operated switch: yes Switch (type): Integral, on/off/door-operated switch mode

Rated insulation voltage:	500 V DC/1s
Rated impulse withstand voltage, phase to earth:	1000 V AC
Rated impulse withstand voltage, phase to phase:	500 V AC
Protection category:	I (PE conductor)
Connection options:	Power supply via connectors Through-wiring (creating rows of lights)
Light – installation type:	Screw-fastening
Light cover:	yes
Packs of:	1 pc(s).
Weight/pack:	2.52 kg
EAN:	4028177320758
Customs tariff number:	94054095
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity