

Rittal – The System.

Faster – better – everywhere.

Door-operated switch – SZ 4315.710

Date : Jan 25, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Door-operated switch – SZ 4315.710

created: 25.01.2019 build on www.rittal.com/uk-en



Product features

Dimensions: Length: 600 mm

Rated operating voltage: 400 V

Installation options: for compact light

For rated current (max.): 240 V AC, 2,5 A

Equipment (electrical): Colour of cable: Yellow

Rated insulation voltage: 400 V AC

Rated impulse withstand voltage, phase to phase: 6000 V AC

Packs of: 1 pc(s).

Weight/pack: 0.12 kg

EAN: 4028177581371

Customs tariff number: 85444290

ETIM 6.0: EC002626

ETIM 5.0: EC002626

eCl@ss 8.0/8.1:	27189266
eCl@ss 7.0/7.1:	27119116
eCl@ss 6.0/6.1:	27119116
eCl@ss 5.1/5.1.4:	27189241
Product description:	SZ Door-operated switch, with connection wire for compact light, L: 600 mm, yellow
Approvals	
Approvals:	CCC
Certificates:	EAC
Declarations:	Declaration of conformity