

enclosure equipment


for Atlantic and Atlantic stainless steel enclosures



0367 80



Metal Atlantic enclosure equipped with document holder Cat. No. 0365 80/81



0367 81

Enclosure and equipment selection chart **p. 8-9**
 Technical characteristics **p. 20**

Lina 25 sectioned uprights

Pack	Cat. Nos.	For enclosures height (mm)	Length (mm)	Section
5	0361 50	300	237	
5	0361 51	400	337	
5	0361 52	500	437	
5	0361 53	600	537	
5	0361 54	700	637	
5	0361 55	800	737	
5	0361 56	1000	937	
1	0361 58	1200	1137	
1	NEW 0361 59	1400	1337	

Lina 25 rail

Rail
 For fixing onto uprights with clip nut Cat. No. 0364 42 and screw-washer Cat. No. 0367 75 see **p. 21**

Pack	Cat. Nos.	For enclosures width (mm)	Crosspiece length (mm)	Section
10	0367 80	300	243	
10	0367 81	400	343	
10	0367 82	500	443	
10	0367 83	600	543	
10	0367 84	800	743	

Rail to be cut, length 2 m

10	0374 02	EN 60715
10	0374 07	Symmetrical depth 15 mm

Copper bars

Pack	Cat. Nos.	Cross-section (mm)	Max. intensity allowed (A)	Tapped holes		Length (mm)
				Ø mm	Pitch	
10	0373 88	12 x 2	110	M5	18	990
10	0373 89	12 x 4	160	M5	18	990

Connectors for bars with tapped holes

1 or 2 conductor from 1.5 to 10 mm² (supplied with Ø5 mm screws)



Non perforated copper bar

Pack	Cat. Nos.	Cross-section (mm)	Max. intensity allowed (A)	Length (mm)
10	0373 49	12 x 4	180	991.5

Connectors for bar Cat. No. 0373 49


100	0373 60	1.5 to 4 mm ²
10	0373 61	6 to 16 mm ²
10	0373 62	10 to 35 mm ² (supplied with M6 CHC Ø5 mm)



Self adhesive document holder (for plans)

Open - RAL 7035

Pack	Cat. Nos.	External dimensions		Internal dimensions		
		Width (mm)	Height (mm)	Width (mm)	Height (mm)	Depth (mm)
20	0365 80	340	235	310	200	18
20	0365 81	260	165	230	130	18



1: Protective conductor per connector (art. 12 of French decree of 14/11/89)